

## Product information | TECHNICAL DATA SHEET

### ANTI RUST PRIMER

150ml: 4 oz - 117 g. 400 ml: 11 Oz - 305 g

#### GENERAL DESCRIPTION

Anti rust primer formulated with acrylic resins and corrosion inhibitor pigments, makes it ideal for protecting any iron surface.

#### FEATURES

- Fast drying.
- Good elasticity.
- Easy of application and recoating.
- Good adherence.
- Does not contain lead.
- High covering power.
- Very high resistance to outdoor exposure.
- High anti-corrosion power.

#### APPLICATIONS

Suitable as primer in spray paint systems. Its anticorrosive power makes it ideal as a primer coat for protecting any iron surface.

- Automotive industry
- Industrial applications
- Metal structures
- DIY
- Mantenimiento

#### INSTRUCTIONS FOR USE

- Shake can vigorously for one minute after hearing mixer noise.
- Thoroughly clean, degrease, and dry the object to be painted. On rusty metallic surfaces, remove corrosion using a wire brush.
- Apply thin coats for best results, always thin layers is better than one thick, paintable after ten minutes with the same paint.
- Disconnect the electrical appliance before painting. Use it in well ventilated areas.
- Request safety data sheets.

#### PHYSICAL PROPERTIES

Brinder type:	Acrylic
Color:	Gray, Red
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Total drying (ASTM D-1640 ISO 1517):	30'
Thickness of dry layer (ASTM D-823 ISO 2808):	15 µ/layer
Adherence (ASTM D-3359 ISO 2409):	B
Theoretical Coverage (pintado en continuo):	2,5 m² for 400 ml 0,70 m² for 150 ml
Thinner:	Butyl Acetate
Product life:	>2 Years
Recoating:	After 10'
Painted resistance to heat:	160°C
Applocation conditions:	T° environment min 8°C T° surface min 5-50°C Humidity max 85% R.H.P

\*Adherence tests were performed on steel.

#### APPARENCE

**DONUT**  
Indicates  
the paint color



**LID**  
Protects the valve  
and the nozzle.

#### LABEL



400 ml

EX0140115 Imp. Antiox. Gris

EX0140131 Imp. Antiox. Roja

150 ml

EX0130115 Imp. Antiox. Gris

#### CAP SYSTEM



Medium Cap

#### PACKAGING

Nominal capacity 400ml.  
Heat resistance of packaging : <50°C  
Propellant: DME

Box (6 units)  
205 X 140 X 200 mm.



---

**WARNINGS**

- Extremely flammable aerosol.
- Pressurised container: may burst if heated.
- Causes serious eye irritation.
- May cause drowsiness or dizziness.
- Repeated exposure may cause skin dryness or cracking.
- If medical advice is needed, have product container or label at hand.
- KEEP OUT OF REACH OF CHILDREN.
- Read label before use.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Do not spray on an open flame or other ignition source.
- Do not pierce or burn, even after use.
- Use only outdoors or in a well-ventilated area.
- Do not breathe aerosol.
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Protect from sunlight.
- Do not expose to temperatures exceeding 50°C/122°F.
- Dispose of contents/container in a safe way.
- Contains n-butyl acetate and Ethyl acetate.

---

**CAUTION**